



# MAN TGM 18.280 4x4, 5,000L DIESEL SERVICE TRUCK | CT027

## PRODUCT SUMMARY

### MAN TGM 18.280 4x4, 5,000L Diesel Skid Mounted Service Truck Specifications:

- 280 hp Turbo charged and inter cooled 4 cycle diesel engine with exhaust retarder
- EURO IV compliant
- Alloy SRS approved bulbar
- Pre cleaner stack and bowl
- Automated manual synchromesh transmission
- Air conditioned high roof cabin
- ROPS to AS 2294 Serial #3869
- ISRI suspension seat
- Passenger seat with retractable seat belts

- Fabric seats with canvas seat covers
- AM/FM radio
- East West mirrors and spot mirrors
- Spring front and rear suspension
- Non asbestos brake linings
- Air dryer
- Spring applied emergency and parking brake
- Headlights on with ignition
- Continental radial flotation tyres
- Wheel chocks
- Spare wheel
- Jack and wheel brace
- Standard tint laminated windscreen
- Tropical tinted rear and side windows
- Safety signage
- High visibility striping 75mm
- Two way radio power supply
- 2 x 9kg Fire extinguishers
- Auxiliary lighting
- Reverse alarm
- Roof mounted amber beacon
- Whip aerial
- Lockable isolator
- Start Isolator
- Jump start receptacle
- Passed road worthy for Western Australia
- Tray Specifications:
  - Heavy duty steel tray 5.2 m x 2.5m complete with 5mm checker plate floor
  - Cab protection rack 1m high
  - Channel combing
  - Mudguards and mud flap
  - Drop sides
  - Side and rear step access
  - Full sub frame 75x75x6 for crane
  - Steps to front with grab handle to cab rack and removable grab handle to combing
- Crane Specifications:
  - Hiab 088-B2 Duo Crane
  - Hydraulic outreach to 7.6 meters
  - Out Reach/lifting capacity: (ADS)
  - 2700 kg @ 2.9m
  - 2000 kg @ 3.8m
  - 1380 kg @ 5.4m
  - 1020 kg @ 7.3m
  - Space 3000 overload protection system
  - Emergency stops located on crane controls (both sides)

## SAFETY FEATURES

- Safety signage
- High visibility striping 75mm
- 2 x 9kg Fire extinguishers
- Auxiliary lighting
- Reverse alarm
- Roof-mounted amber beacon
- Lockable isolator
- Start Isolator
- Jumpstart receptacle

## TRAY SPECIFICATIONS

- Heavy-duty steel tray 5.2 m x 2.5m complete with 5mm checker plate floor
- Cab protection rack 1m high
- Channel combing
- Mudguards and mud flap
- Drop sides
- Side and rear step access
- Full subframe 75x75x6 for crane
- Steps to the front with grab handle to cab rack and removable grab handle to combing

## PRODUCT SPECIFICATIONS

<b>AXLES</b>	4x4
<b>CAPACITY</b>	5000L
<b>MAKE</b>	MAN
<b>TYPE</b>	Skid Mounted Module