



## TANDEM AXLE TAG TRAILER | TR010

### PRODUCT SUMMARY

#### Plantman Tandem Axle Tag Trailer Specification:

- Overall length (from centre of tow hitch to rear of hydraulic cylinders on the ramps) 10500mm x 2490mm wide
- Flat floor length of 8500mm long x 2490 wide
- 1 x heavy duty drawbar length of 1600mm
- Heavy-duty trailer ramps
- Secondary securing bars for the ramps
- Complete set of hydraulics to operate ramps that include 2 x double acting cylinders complete with safety check valves, 24volt double-acting power pack with control valve mounted to trailer that is charged off the truck
- Set of batteries charged through an Anderson plug from the truck

- Tray floor is constructed from 75 x 40 channel with 3mm checker plate, 125x50 channel coamings, and 32mm heavy wall tie rails
- 32mm heavy wall tie rails down each side of the trailer
- 8 x 4 tonne recessed tie-down rings for tying off equipment
- 9 x 255 R70 22.5 low profile tubeless wheels and tires includes spare
- Spare wheel holder
- 9 x Steel spider rims include spare
- 4 x Spacer bands
- 2 x GTS 10 stud 225 PCD axles
- 1 x Tandem axle underslung spring suspension kit
- 1 x Tandem axle Westinghouse brake kit
- Single-speed heavy duty wind down leg

## PRODUCT SPECIFICATIONS

<b>CAPACITY</b>	10.5m
-----------------	-------